



PRODUCT	Acrybase S
MISSION	Solvent-based acrylic primer
CHARACTERISTICS	Acrybase S is a solvent-based acrylic primer that improves adhesion of acrylic systems (Acryroof Plus, Dermacem) on low or non porous surfaces such as stoneware, fibre cement, bituminous membranes, metal or cement decks.
APPEARENCE	Transparent colourless low-viscosity liquid; typical odour of organic solvents

CHARACTERISTICS OF THE LIQUID PRODUCT

CHARACTERISTICS	VALUE	TOLERANCE	U.M.
Specific weight	0,91	± 0,02	Kg/dm ³
Dry mass residue	18	± 1	%
Efflux time at 23° C (with Ford cup, hole n°3)	29	± 2	sec

APPLICATION INSTRUCTIONS

TOOLS	THINNING	TYPE OF THINNER	TOOL CLEANING
Brush	Ready to use		DIL S1
Roller	Ready to use		DIL S1
Spray	Ready to use		DIL S1

LAYING SURFACE	Ensure that the deck is clean and dry removing all traces of dirt, grease and loose parts, if necessary, repair excessive roughness and ensure sufficient slope to ensure rainwater runoff.
----------------	---

CONSUMPTION	Coverage is generally approx. 100 ml/sqm for non-porous decks, approx. 150 ml/sqm. for low-porous decks and approx. 220 ml/sqm. for cement decks.
-------------	---

APPLICATION INSTRUCTIONS	Environmental and deck temperature limit during application: MIN 10°C - MAX 40°C. Product must be perfectly dry before exposure to fog, rain or frost.
--------------------------	--

DRYING AT 23° C AND 50 % U.R.	<p>On surface: 1 h To touch: 2 h Interval between coatings: 24 h</p> <p>The times shown are intended for standard laboratory conditions. Drying times are strongly affected by weather conditions; high temperatures and direct sunlight reduce the drying times; areas in shadow, low temperatures and high humidity increase the drying times. In winter the product should be laid in the middle of the day when it is warmer. Ensure that the previous layer has dried properly before applying the next layer.</p>
-------------------------------	---





PACKAGING INSTRUCTIONS	COLOURS AVAILABLE Transparent	PACKAGING 5 – 10 Lt
STORAGE INSTRUCTIONS	STORAGE TEMPERATURE MIN 3° C – MAX 40° C	STABILITY IN THE ORIGINAL PACKAGE 24 months
SAFETY STANDARDS	Please read the safety data sheet carefully before using this product.	