



PRODUCT	<b>Sintomastik</b>
MISSION	Solvent-based bituminous glue for insulating panels
CHARACTERISTICS	Sintomastik is a solvent-based bituminous sealant consisting of distilled bitumen and elastomers. The product is used to glue horizontal and vertical insulating panels in mineral wool, glass wool, polyurethane panels, polyester, etc... double-sanded bituminous membranes (without polyethylene release agent film) on cement or wood surfaces (or in any case transpiring surfaces). If the product is applied vertically, prop up during drying
APPEARANCE	Black thixotropic paste.

**CHARACTERISTICS OF THE LIQUID PRODUCT**

CHARACTERISTICS	VALUE	TOLERANCE	U.M.
Specific weight	1,09	± 0,05	Kg/dm <sup>3</sup>
Dry residue	75	± 1	%

**APPLICATION INSTRUCTIONS**

TOOLS	THINNING	TYPE OF THINNER	TOOL CLEANING
Spatula	Ready to use		DIL S1
Toothed spatula	Ready to use		DIL S1

<b>APPLICATION METHOD</b>	Sintomastik may be applied in spots or strips. In the first case, the glue spots (40/50 g each) should be spaced by about 40/50 cm. while in the second case the strips should be spaced by about 40 cm. with length of approx. 5 cm. and thickness of 3 - 4 mm.
---------------------------	--

<b>LAYING SURFACE</b>	Clean and dry.
-----------------------	----------------

<b>CONSUMPTION</b>	Average coverage per sq.m. is about 0,5 Kg
--------------------	--

<b>APPLICATION INSTRUCTIONS</b>	Environmental and deck temperature limit during application: MIN 5°C - MAX 40°C.
---------------------------------	--

**CHARACTERISTICS OF THE DRY PRODUCT**

CHARACTERISTICS	VALUE	TOLERANCE	U.M.
Adhesion (on fibre cement)	0,9	± 0,1	N/mm <sup>2</sup>

<b>PACKAGING INSTRUCTIONS</b>	<b>COLOURS AVAILABLE</b> Black	<b>PACKAGING</b> 20 Kg
<b>STORAGE INSTRUCTIONS</b>	<b>STORAGE TEMPERATURE</b> MIN -5° C – MAX 40° C	<b>STABILITY IN THE ORIGINAL PACKAGE</b> 24 months
<b>SAFETY STANDARDS</b>	Please read the safety data sheet carefully before using this product.	

