



PRODUCT	Reflex W
MISSION	Reflecting aluminium paint in water emulsion for bituminous membranes
CHARACTERISTICS	Reflex W is a water-based aluminium paint used to protect prefabricated or liquid bituminous membranes such as Dermarubber, Dermacem, etc. Thanks to its formulation, Reflex W reflects UV rays preventing damage and reducing the temperature of the membrane. Reflex W is also ideal for protecting metal surfaces such as tanks, pipes, poles, metal structures etc.
APPEARANCE	Low-viscosity aluminium coloured liquid

CHARACTERISTICS OF THE LIQUID PRODUCT

CHARACTERISTICS	VALUE	TOLERANCE	U.M.
Specific Weight:	1.00	± 0.1	Kg/cu.dm
Viscosity (with DIN cup 4)	40		sec
pH	7	± 0.5	

APPLICATION INSTRUCTIONS

TOOLS	THINNING	TYPE OF THINNER	TOOL CLEANING
Brush	Ready-to-use		Water
Roller	Ready-to-use		Water
Spray gun	Ready-to-use		Water

LAYING SURFACE	Bituminous decks should be allowed to cure for at least 3-4 weeks before applying Reflex W. Metal surfaces should be cleaned thoroughly removing all traces of oil, dirt and debris. If necessary prepare and repair the deck.
-----------------------	--

CONSUMPTION	About 100 ml/sqm, every coat but this may vary according to the deck. Two coatings are recommended.
--------------------	---

APPLICATION INSTRUCTIONS	Ambient temperature MIN 5° C MAX 40° C Ensure that the product has cured thoroughly before exposure to fog, rain or frost. Do not apply the product on decks where pooling is present. Mix the product until it is perfect smooth before application
---------------------------------	---



DRYING AT 23° C AND 50 % U.R.	Dry dust free: 30' Fully cured: 2 h The times indicated refer to standard laboratory conditions. Drying times are strongly affected by the weather; high temperatures and exposure to direct sunlight accelerate drying; shadow, low temperatures and high humidity delay drying. During winter it is advisable to lay the product in the middle of the day when it is warmer. Always ensure that the previous layer has cured perfectly before applying a new coating.
--------------------------------------	---

PACKAGING INSTRUCTIONS	COLOURS AVAILABLE Aluminium	PACKAGING 5 – 10 – 16 Lt
STORAGE INSTRUCTIONS	STORAGE TEMPERATURE MIN 5° C – MAX 40° C	STABILITY IN THE ORIGINAL PACKAGE 18 months
SAFETY STANDARDS	Please read the safety data sheet carefully before using this product.	



La Casali S.p.A. si riserva di modificare senza alcun preavviso i dati contenuti nella presente scheda tecnica. L'uso, sia proprio sia improprio, del prodotto indicato nella presente scheda, ricade sotto l'esclusiva responsabilità dell'utilizzatore che è tenuto a una valutazione preventiva dell'idoneità del prodotto alle proprie esigenze, nonché, alla massima cura nell'utilizzo di qualsiasi prodotto chimico. L'Ufficio Tecnico della Divisione Sintetici Casali resta a disposizione per chiarimenti e per rispondere a richieste specifiche derivanti dalla natura dell'opera (tel. 071 9162095).