



PRODUCT	Additive AS
MISSION	Synthetic non-slip synthetic filler for paints
CHARACTERISTICS	Additive AS is a very fine synthetic filler for paints that ensures excellent resistance to abrasion and improves surface grip making it non-slip. Additive AS is used with Pavisint Finish 90 in the Pavisint SL 75 – AS system, or with the polyurethane paint Polytop for painting Polyroof terraces and balconies.
APPEARANCE	White powder

CHARACTERISTICS OF THE LIQUID PRODUCT

CHARACTERISTICS	VALUE	TOLERANCE	U.M.
Density	1.02	± 0.05	Kg/cu.dm
Granulometry	< 32 µm < 100 µm < 250 µm	≤ 2 ≥ 45 100	%
Shore D hardness	75		

APPLICATION METHOD	Before adding Additive AS to the paint, mix the components A and B together and stir until the mixture is perfectly smooth and lump-free, then add the non-slip filler. If the paint is very liquid, remember to stir the mixture occasionally to prevent Additive AS from settling on the bottom.
---------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

PACKAGING INSTRUCTIONS	COLOURS Neutral	PACKAGING 50 gr. can for 5 Kg paint can and 100 gr. can for 10 Kg paint can
STORAGE INSTRUCTIONS	STORAGE TEMPERATURE MIN 3° C MAX 35° C	STABILITY IN THE ORIGINAL PACKAGE 24 months
SAFETY STANDARDS	Please read the safety data sheet carefully before using this product.	