



PRODUCT	Root Stop Additive
MISSION	Liquid additive for solvent and water based products
CHARACTERISTICS	This product is a liquid additive used with waterproofing liquids both in water emulsion (Acryroof Plus, Dermarubber, Dermacem, exc.) both solvent based (Dermarubber S). Once mixed, Root Stop Additive gives an excellent resistance to the roots attack, avoiding the perforation of the waterproofing coating, according to the EN 13498, so improve the range of usage of the Casali's – T&C's waterproofing liquid materials on roof gardens, planters, retaining walls.
APPEARENCE	Brown liquid

CHARACTERISTICS OF THE LIQUID PRODUCT

CHARACTERISTICS	VALUE	TOLERANCE	U.M.
Specific weight	1,05	± 0.05	Kg/dm ³

APPLICATION METHOD	Desperse Root Stop Additive in the waterproofing product with a mixer or a drill until reach an homogeneous mixture.
---------------------------	--

PACKAGING INSTRUCTIONS	COLOURS Neutral	PACKAGING Plastic can with predosed quantity for 20 Kg; 8 pieces box
STORAGE INSTRUCTIONS	STORAGE TEMPERATURE MIN 5° C MAX 35° C	STABILITY IN THE ORIGINAL PACKAGE 36 months
SAFETY STANDARDS	Please read the safety data sheet carefully before using this product.	

WARNINGS	Any other uses of Root Stop Additive, that are not specifically described in this technical data sheet, do not guarantee the perforation resistance and we suggest to make some tests to verify the efficacy.
-----------------	---