



PRODUCT	Slate Chips
MISSION	Protective for prefabricated or liquid bituminous membranes
CHARACTERISTICS	Slate Chips is supplied in bulk, in this way you can use it as protective for the waterproofing material during the reparation works especially on roofings. It is usable with prefabricated bituminous membranes and with liquid bituminous membranes such as Dermarubber S/P, Dermarubber, etc.
APPEARENCE	Coloured chips

CHARACTERISTICS OF THE LIQUID PRODUCT

CHARACTERISTICS	VALUE	TOLERANCE	U.M.
Density	>1	± 0.05	Kg/dm ³

MAPPLICATION METHOD	In the case of a repair with a prefabricated bituminous membrane, after the flame of the latter to glue it to the support, the heat is reused to dissolve the upper surface and, before being cooled, it is sprinkled with Slate Chips. In the event that liquid waterproofing products are used, the fresh surface can be sprinkled immediately after application of the last abundant coat of waterproofing material.
----------------------------	---

PACKAGING INSTRUCTIONS	COLOURS Natural, white, red, green and other on request	PACKAGING 15 Kg
STORAGE INSTRUCTIONS	STORAGE TEMPERATURE MIN 3° C MAX 35° C	STABILITY IN THE ORIGINAL PACKAGE 36 months
SAFETY STANDARDS	Please read the safety data sheet carefully before using this product.	