



<b>PRODUCT</b>	<b>Booster 120</b>
<b>MISSION</b>	Accelerant liquid additive for synthetic products
<b>CHARACTERISTICS</b>	<p>Booster 120 is a liquid additive used to improve the drying time of synthetic product in water emulsion. Is added in the liquid waterproofing products to allow their application also at low temperatures (3° C) and high level of humidity. Thanks to Booster 120 the products creates a dry film on the surface more quickly that can resist at the atmospheric agents.</p> <p>Booster 120 in prebatched bottles for 20 Kg boxes can be addes at the following products:</p> <ul style="list-style-type: none"><li>- Acryroof Plus</li><li>- Acryroof Plus Fibro</li><li>- Acrytop</li><li>- Acryroof</li><li>- Acryrubber</li><li>- Colorpark Level</li><li>- Colorpark AC</li></ul> <p>At the temperature of 3° C Booster 120, correctly mixed with the product, allows the formation of a superficial dry film after only 2 hours.</p>
<b>APPEARENCE</b>	Yellow liquid

<b>CHARACTERISTICS OF THE PRODUCT</b>			
<b>CHARACTERISTICS</b>	<b>VALUE</b>	<b>TOLERANCE</b>	<b>U.M.</b>
Density	1.05	± 0.05	Kg/cu.dm
pH	9,5 – 10		

<b>APPLICATION METHOD</b>	Mix Booster 120 in the product with the help of a mixer or a drill until obtain an homogeneous mix.
---------------------------	---

<b>PACKAGING INSTRUCTIONS</b>	<b>COLOURS</b> Neutral	<b>PACKAGING</b> Plastic can with premeasured product for 20 Kg boxes; 8 pieces box
<b>STORAGE INSTRUCTIONS</b>	<b>STORAGE TEMPERATURE</b> MIN 5° C MAX 30° C	<b>STABILITY IN THE ORIGINAL PACKAGE</b> 36 months
<b>SAFETY STANDARDS</b>	Please read the safety data sheet carefully before using this product.	

