



PRODUCT	Casaband SA
MISSION	Self-adhesive butyl band for perimeter and expansion joints
CHARACTERISTICS	Casaband SA is a self-adhesive band in butyl rubber that not only ensures excellent adhesion on concrete, gypsum board and marble but even on other rough and absorbing decks on which the liquid waterproofing is to be applied. Casaband SA band may be used with most liquid waterproofing systems (Dermarubber S/P, Dermacem, Acryroof Plus, etc.) and is used as elastic reinforcement when waterproofing floor-wall joints and expansion joints on terraces, balconies, swimming pools, bathrooms, etc.

ACRYFELT T1 60			
CHARACTERISTIC	VALUE	U.M.	TEST
Standard thickness	1,0 – 1,5	mm	
Elongation at longitudinal tensile strength	> 100	N/50 mm	EN 12311-1
Elongation at transverse tensile strength	> 100	N/50 mm	EN 12311-1
Elongation at longitudinal break	> 70	%	EN 12311-1
Elongation at transverse break	> 70	%	EN 12311-1
Specific Weight:	1,4	g/cu.m.	ASTM D 792
Peeling	≥ 90	N	ASTM D 1000
Vertical creep	0	mm	SO 7390
Adhesion strength on concrete	0,9	N/sq.mm	EN 12004-EN 1348
Temperature application range:	0° C / + 40° C		
Service temperature	-30°C / +80°C up to 160°C for up to 24h		

PACKAGING INSTRUCTIONS	Available sizes: - 8 cm x 15 linear meters - 15 cm x 25 linear meters Packaging: 8 rolls box
APPLICATION METHOD	To ensure the perfect adhesion of Casaband SA, above all when dust is present, fix down the dust with a coating of liquid waterproofing applied as primer (see the relevant product data sheet for the thinning %) before applying the self-adhesive band. Once the diluted product has cured thoroughly, lay the self-adhesive band and cover it with liquid waterproofing liquid as is.

