



PRODUCT	Idroprimer
MISSION	Ecological bituminous primer
CHARACTERISTICS	Idroprimer is a primer in water emulsion for bituminous waterproofing materials such as prefabricated and bituminous liquid membranes and hot bitumen with ensures excellent adhesion on any type of surface. The product consists of distilled bitumen, water and additives that ensures rapid drying.
APPEARANCE	Medium viscosity brown liquid

CHARACTERISTICS OF THE LIQUID PRODUCT

CHARACTERISTICS	VALUE	U.M.
Specific weight	0,95 – 1,15	Kg/dm ³
Dry mass residue a 130° C	32 – 37	%
viscosity DIN/4 a 20° C	15 – 20	Sec
pH	11 - 13	

APPLICATION INSTRUCTIONS

TOOLS	THINNING	TYPE OF THINNER	TOOL CLEANING
Brush	Approx. 20%	Water	Water
Roller	Approx. 20%	Water	Water
Spray	Approx. 25%	Water	Water

LAYING SURFACE	Ensure that the deck is clean removing all traces of dirt, grease and loose parts, if necessary, repair excessive roughness and ensure sufficient slope to ensure rainwater runoff
----------------	--

CONSUMPTION	Consumption depends on the absorbing capacity of the laying surface. Generally about 200 gr/sqm for the cement surfaces.
-------------	--

APPLICATION INSTRUCTIONS	Temperature limit during application: MIN 10°C - MAX 40°C
--------------------------	---

DRYING AT 23° C AND 50 % U.R.	On surface: 45' At touch: 1 h e 30' Interval between coatings: 4 h The times shown are for standard laboratory conditions. The drying times are strongly influenced by the weather; high temperatures and direct sunlight accelerate drying; shadows, low temperatures and high humidity levels delay drying. In winter the product should be laid in the warmer hours in the middle of the day. Always ensure that the previous layer has cured properly before applying a new coating.
-------------------------------	--



PACKAGING INSTRUCTIONS	COLOURS AVAILABLE Black	PACKAGING 5 – 10 – 20 Kg
STORAGE INSTRUCTIONS	STORAGE TEMPERATURE MIN 3° C – MAX 40° C	STABILITY IN THE ORIGINAL PACKAGE 24 months
SAFETY STANDARDS	Please read the safety data sheet carefully before using this product.	



La Casali S.p.A. si riserva di modificare senza alcun preavviso i dati contenuti nella presente scheda tecnica. L'uso, sia proprio sia improprio, del prodotto indicato nella presente scheda, ricade sotto l'esclusiva responsabilità dell'utilizzatore che è tenuto a una valutazione preventiva dell'idoneità del prodotto alle proprie esigenze, nonché, alla massima cura nell'utilizzo di qualsiasi prodotto chimico. L'Ufficio Tecnico della Divisione Sintetici Casali resta a disposizione per chiarimenti e per rispondere a richieste specifiche derivanti dalla natura dell'opera (tel. 071 9162095).